



Superfine sander with linear (not rotary) sanding motion.

Pensander PS 13

This superfine sander with linear sanding motion (versus rotary or orbital) operates at 8,000 strokes per minute with a 3/32" (2.5mm) stroke. It is ideal for surfaces, slots and tight corners. Included are four sanding attachments with straight shanks and 4 with angled shanks (four different shapes per shank style) as well as 3 sheets of preprofiled adhesive sanding pads. The sheets are 180, 240 and 400 grit with 5 of each shape per sheet.



Technical data:

Direct voltage	12 - 18V
Speed	8,000 strokes per minute with 3/32" (2.5mm)
Length	6.3" (160mm)
Weight	0.29 lb (130g)

Note:

An AC adapter of at least 12 - 18V DC and 1.0A is required. We recommend PROXXON power supplies NG 2/S or NG 5/E. The electronic speed control on the NG 5/E unit allows the selection of different speeds for different applications and materials

NO 28 594

⚠ WARNING:

This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.



Video PS 13

Replacement Sandpaper for the PS 13

Three sheets, each with 20 pads (5 each of the four shapes, adhesive).

NO 28 822	180 grit
NO 28 824	240 grit
NO 28 826	400 grit