



***Useful accessories for lathe and milling systems.***

***Nearly all accessories are supplied in wooden boxes. For proper and value preserving storage!***



## **Dividing attachment TA 250**

**For precision lathe PD 250/E, mill and drill head PF 230 and micro miller FF 230.**

For accurate machining of circular work pieces (e.g. production of gear wheels). Supplied with two dividing discs (40 and 48 teeth), enabling standard divisions of 2 - 3 - 4 - 5 - 6 - 8 - 10 - 12 - 16 - 20 - 24 - 40 und 48. The taper of the dividing attachment is the same size as that of the main spindle of the PD 250/E lathe, thus 3 jaw chuck (NO 24 034) and 4 jaw chuck (NO 24 036) may be mounted. Horizontal fitting (e.g. on the cross-slide of the lathe) and vertical fitting (on the machine bed) are possible. With matching nuts and screws for fixation in MICROMOT standard T-slots (12 x 6 x 5mm). Supplied in a wooden box with sliding lid.



**NO 24 044**

## **Radius cutting attachment**

Is mounted on the cross slide in place of the tool holder. For producing convex and concave shapes, for turning radii or 3/4 spheres with radii of 32mm max. Height adjustable tool holder (boring tool tip adjustable from 30 through 45mm above cross slide) for use with FD 150/E, PD 250/E, PD 400 and older PROXXON lathes. Dimensions: base plate 67 x 50mm, height 55mm. Including finishing cutter 8 x 8 x 80mm. In wooden box with sliding lid.



**NO 24 062**

### **Dividing head for MICRO miller MF 70 and MICRO compound table KT 70**

For machining circular work pieces, manufacturing off-set holes and milled out portions, milling key surfaces, four-sided, six-sided materials, etc. Absolute accurate division due to nonius at the base body. With reversed chuck jaws: Capacity inside 1.5 to 32mm, outside 12 to 65mm. Bore of 11mm (for processing longer spindles in a vertical position). With fastening bores for horizontal and vertical mounting and suitable slot nuts and fastening screws for mounting to the MICRO miller MF 70 and the MICRO compound table KT 70. Size 72 x 64 x 38mm. In wooden box with sliding lid.



**NO 24 264**

### **Self-centering 3-jaw chuck (not depicted)**

Identical to chuck of lathe PD 250/E. High quality clamping fixture as per DIN 8386, Class 1 (concentricity accuracy 0.04mm). Capacity through reversing jaws from 2 - 75mm. Suitable for PD 250/E and the dividing attachment NO 24 044.

**NO 24 034**

### **Die holder for round dies**

**For threads M 3 - 4 - 5 - 6 - 8 and 10.**

With holder Ø 10mm for mounting in the tailstock drill chuck of the lathe. The holder is held by hand while cutting the threads. Neatly packed in wooden box with sliding lid.

**NO 24 082**



### **Tool holder for rotary tools**

**Made of steel with standard 20mm MICROMOT collar size.**

For precise clamping of rotary tool IBS/E or LBS/E in the tool post of the lathe. Shaft 8 x 10mm. Total length 65mm.

**NO 24 098**



### Precision-milled steel machine vices.

Perfectly rectangular. To be placed sideways and on the end face. With matching nuts and screws. Supplied in wooden box with sliding lid.

#### PM 40

Jaw width of 46mm. Clamping capacity 34mm. Total length 70mm.

**NO 24 260**



#### PM 60

Jaw width 60mm. Clamping capacity 42mm. Total length 100mm.

**NO 24 255**



### Step clamp set of steel

#### 2 step blocks and clamps each.

With matching slot nuts and fastening screws for T-slots as per MICROMOT standard (12 x 6 x 5mm). In wooden box with sliding lid.

**NO 24 256** For work pieces up to 20mm thickness

**NO 24 257** For work pieces up to 35mm thickness



### Precision V-blocks

#### Used to clamp various work pieces.

Made from hardened steel, precision ground in pairs. Four different depths of prism incisions V, all at 90°. Size 50 x 30 x 30mm. The solid clamp and knurled knob ensure superb securing of the workpiece. Supplied in a wooden box with sliding lid.

**NO 24 262** 2 pieces



### 14-piece parallel supports set

#### Ground in pairs.

For adjusting work on drilling machines, lathes and milling machines. Made of high-alloy, hardened steel (58 - 62 HRC). Parallel accuracy 0.02mm. 2 each of 8 x 10, 15, 20, 25, 30, 35 and 40mm. Length 100mm. Packed in a wooden box.

**NO 24 266**



### Edge finder set

Used for fast and accurate location of starting point of work pieces with respect to the machine spindle on milling machines. Size 6 x 6 x 50mm and 6 x 5 x 75mm. Comes in wooden box with sliding lid.

**NO 24 434**



## Cutting tools of high quality cobalt HSS steel, ground.

### HSS boring tool set, 6 pieces

One each cutter for 60 degree (metric) and 55 degree (Whitworth) inside threads, 1.3mm - 2.65mm and 4mm. Shaft of Ø 6mm. Length 95mm. The cutters are held by a tool holder (9 x 9mm) that mounts to the tool post of either PD 230/E, PD 250/E or PD 400. Comes in wooden box with sliding lid.



**NO 24 520**

### 6-piece turning tool set for precision lathe FD 150/E

One each boring, roughing out, parting, finishing, right and left cutter. Size 6 x 6 x 65mm. Supplied in wooden box.



**NO 24 524**

### Five piece set

One each roughing out, parting, finishing cut, left and right cutter. Comes in wooden box with sliding lid.

8 x 8 x 80mm (for PD 230/E and PD 250/E)

**NO 24 530**

10 x 10 x 80mm (for PD 400)

**NO 24 550**



### Three piece thread cutting set

One cutter for external thread ❶, one for internal thread ❷ (both ground to 60°, metric), one general cutting ❸. Supplied in wooden box with sliding lid.

8 x 8 x 80mm (for PD 230/E and PD 250/E)

**NO 24 540**

10 x 10 x 80mm (for PD 400)

**NO 24 552**



### Cutter set with tungsten inserts

Three holders (90mm long):

❶ for roughing out;

❷ for longitudinal work;

❸ for 90mm boring bar, holes from 12mm.

Standard tungsten inserts, 55°, plated (commercially available version). Three additional inserts securing screw and key TX 8 are included.

8 x 8mm (for PD 230/E and PD 250/E)

**NO 24 555**

10 x 10mm (for PD 400)

**NO 24 556**

### Tungsten disposable tips (not depicted)

For the holders as described above.

**NO 24 557**

Ten piece set



### Milling cutter set (2 - 5mm)

All cutters with 6mm shaft. Cutters of Ø 2 - 3 - 4 and 5mm. Double fluted according to DIN 327. Made of HSS-Co5. Comes in wooden box with sliding lid.

**NO 24 610**



### Milling cutter set (6 - 10mm)

4 cutters Ø 6 - 7 - 8 and 10mm. Four flute design according to DIN 844. Shafts 6 and 10mm respectively. Made of HSS-Co5. Comes in wooden box with sliding lid.

**NO 24 620**



### Tungsten milling cutters

With two flute cutters and fishtail profile (cutting to the centre). Enables lowering into non-bored work pieces. For grey-cast iron, hardened cast iron, steel, cast steel, brass, aluminium, glass, plastic and carbon fibre. One piece each 1 - 2 and 3mm. Shaft diameter 3mm.

**NO 27 116** 3 pieces



### Tungsten milling cutters, separately

See description above.

**NO 28 758** Ø 1mm

**NO 28 759** Ø 2mm

**NO 28 761** Ø 3mm

### Three piece centre drill set

Made of HSS steel. DIN 333 (type A) 60°. Complete set centre drills with sizes of 2 - 2.5 and 3.15mm.

**NO 24 630**



See us on YouTube!