






With electronically adjustable speeds from 820 to 2,460 ft/min for optimal control. Ideal for wet sanding, too.

Disc Sander TSG 250/E

For sanding, polishing, de-burring and beveling of hard and soft wood, non-ferrous metal, steel, plastic (also Plexiglas and fiberglass reinforced plastics), cork and rubber. Sands long edges, end sections, radii, miters, and by turning work piece over, accurate flat surfaces at right angles. The electronic speed control ensures optimal results on multiple types of material.



Sturdy construction:
Main body of ribbed die-cast aluminum (no steel tube or sheet metal construction) with machined aluminum die-cast work table.



The table tilts 15° inwards and 45° outwards (a scale facilitates accurate adjustment) and has a slot for the adjustable miter gauge. Disc provided with a silicon film ensuring that affixed sanding discs can be removed effortlessly after use. Two additional square silicon films for storage and reuse of used sanding discs are included. A simple chart indicates the recommended speeds on different materials.

Technical data:

Speed	820 to 2,460 ft/min (belt drive 7.3 : 1 reduction ratio)
Disc Diameter	9 27/32" (250mm)
Max. Sanding Height	5 5/16" (135mm)
Table Size	10 13/16" x 4 1/8" (275 x 105mm), adjusts 15° in, 45° out
Overall Size (w/o table)	3" x 11" x 9" (330 x 280 x 230mm)
Volts	110 - 120V AC, 60Hz

Comes with miter gauge and two each 80 and 240 grit sanding discs.

NO 38 060



See us on YouTube!



⚠️ WARNING:

This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.



A dust collection adapter for attaching a vacuum cleaner or dust extractor is included.

Accessories for the Disc Sander TSG 250/E

Self-Adhesive Corundum Sanding Discs for TSG 250/E

Industrial quality. For sanding soft and hard woods, chipboards, fibre boards, non-ferrous metals, steel, plastic, cork, rubber and minerals. Ø 9 27/32" (250mm). Includes silicone film for storing used sanding discs.

NO 28 970	80 grit	5 discs
NO 28 972	150 grit	5 discs
NO 28 974	240 grit	5 discs



Self-Adhesive Silicone Carbide Sanding Discs for TSG 250/E

For sanding non-ferrous metals, steel, glass, PC cards, plastics and ceramics. Ø 9 27/32" (250mm). Includes silicone film for storing used sanding discs.

NO 28 976	320 grit	5 discs
-----------	----------	---------



Self-Adhesive Silicone Film for easy sanding disc replacement

For retrofitting older disc sanders TG 250/E (production before 2008 with serial no. up to 7825). Is attached to the sanding disc. Ensures that affixed sanding discs can be removed effortlessly after use. Ø 9 27/32" (250mm). With 4 square silicone films for storage and reuse of used sanding discs.

NO 28 968

